

Wibblue

Detect more



**In cabinet Ethernet
connected Bluetooth,
BLE, WiFi, and LAP
MAC capture module**

www.wibblue.com

WiFi, Bluetooth
classic, BLE and
hidden BT LAP
scanning

Separate
RF modules

Compact size and
low cost

Roads Connect
management

12V-24V DC

Addinsight
compatible

Removable smart
card for config

10/100 Ethernet

- 10°C to 65°C

Compare Bluetooth detections

Wibblue detects 10x more than classic Bluetooth devices.

The extra detections allow more accurate travel time calculations.

With 4 separate RF modules, Wibblue continuously scans Classic Bluetooth and adds Bluetooth Low Energy, WiFi and LAP hidden Bluetooth detections.

Higher detections are achieved as no time slicing is required with separate RF modules.



Classic Bluetooth only



Wibblue detections

Wibblue IC Specifications

Voltage	12-24V DC
Power	3W
Dimensions	39H x 147W x 95D mm (including mounting flange)
Mounting	Flange or DIN rail
Temperature	-10°C to +65°C
Interfaces	1 x Ethernet 10/100 3 x Bluetooth, BLE , WiFi (RP-SMA) 1 x BT LAP (ubertooth type) detector (RP-SMA) 1 x Smart Card 1 x USB Console
Management	Local USB, remote GUI and roads connect UI

Sales and service
www.wibblue.com

